



FULLY LOADED WITH ALL KINDS OF STAYING POWER.

GROUND SPEEDS UP TO **11.5 MPH**

MOWS UP TO **8.4** ACRES PER HOUR

23, 27, 34 & 38 hp Kohler® Command™ V-Twin, 29 hp Kohler Command V-Twin EFI and 24 & 29 Kawasaki® V-Twin and 29 Kawasaki V-Twin Propane engines.

48," 52," 60" & 72" full-floating UltraCut™ Series 6 cutting decks.

Exmark® exclusive Parker unitized pump and wheel motor system with no hoses.

Heavy-duty canister air filtration system.

High-capacity 12-gallon, single fuel tank with single fill location.



power, multiplied.



BEST-SELLING BRAND OF MOWING EQUIPMENT FOR THE LANDSCAPE PROFESSIONAL.

EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Lazer Z® are registered trademarks, and UltraCut™ is a trademark of Exmark Mfg. Co., Inc. ©2011 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2011.



LAZER Z[®] X-SERIES SPECIFICATIONS

MODEL NUMBER	ENGINE	SIZE	DECK	WEIGHT	LENGTH	HEIGHT	WIDTH	
							DEFL. DOWN	DEFL. UP
LZX23KC486	23 hp Kohler [®] Command™	48"	UltraCut™ Series 6	1125 lbs	79.2"	70.5"	59.6"	51.8"
LZX24KA526	24 hp Kawasaki [®] V-Twin	52"	UltraCut Series 6	1116 lbs	79.2"	70.5"	64.8"	56.3"
LZX27KC526 ²	27 hp Kohler Command	52"	UltraCut Series 6	1116 lbs	79.2"	70.5"	64.8"	56.3"
LZX27KC606 ²	27 hp Kohler Command	60"	UltraCut Series 6	1195 lbs	83.1"	70.5"	72.8"	62.5"
LZX29KA606 ¹	29 hp Kawasaki V-Twin	60"	UltraCut Series 6	1212 lbs	83.1"	70.5"	72.8"	62.5"
LZX29EK606 ^{1,2}	29 hp Kohler EFI	60"	UltraCut Series 6	1212 lbs	83.1"	70.5"	72.8"	62.5"
LZX29PKA606	Kawasaki FX901V Propane	60"	UltraCut Series 6	1360 lbs	83.1"	70.5"	72.8"	62.5"
LZX34KA606 ¹	34 hp Kohler Command	60"	UltraCut Series 6	1260 lbs	83.1"	70.5"	72.8"	62.5"
LZX34KC726 ¹	34 hp Kohler Command	72"	UltraCut Series 6	1292 lbs	86.1"	70.5"	84.9"	73.5"
LZX38KC606 ¹	38 hp Kohler Command	60"	UltraCut Series 6	1244 lbs	83.1"	70.5"	72.8"	62.5"
LZX38KC726 ¹	38 hp Kohler Command	72"	UltraCut Series 6	1276 lbs	86.1"	70.5"	84.9"	73.5"

¹Factory-installed full suspension seat also available. Special order only. ²Units are carb-compliant.

POWER COMPONENTS	ENGINE	24 and 29 hp Kawasaki V-Twin; 23, 27, 34 and 38 hp Kohler Command V-Twin; 29 hp Kohler Electronic Fuel Injection (EFI); Kawasaki FX801V V-Twin Propane engines. Kohler engines governed to 3,750 and Kawasaki engines governed to 3,750.
	AIR FILTER	Heavy-duty canister air filtration system.
	DRIVE SYSTEM	Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 16 cc pumps and 17.1 cubic inch motors on 60" & 72" models. 12 cc pumps and 14.5 cubic inch motors on 48" & 52" models.
	SPEED	Infinitely variable speed selection from 0–11.5 mph (18.5 kmph) forward, 0–6 mph (9.7 kmph) reverse on 60" & 72" models. 0–10.0 mph (16.1 kmph) forward, 0–5.5 mph (8.9 kmph) reverse on 48" & 52" models.
	PTO ENGAGEMENT	MagStop Electromagnetic 250-ft-lbs clutch with spot brake (60" & 72" model with engines larger than 31 hp). MagStop Electromagnetic 200-ft-lbs clutch with spot brake (48," 52," 60" & 72" models with engines less than 31 hp).
	FUEL CAPACITY	High-capacity, 12-gallon, single fuel tank with single fill location. For propane units, capacity is 43.5 lbs.
	DRIVE-WHEEL RELEASE	Allows unit movement without engine running.
	SAFETY PACKAGE	Operator Presence Controls (OPC) and drive system interlock.
	ROLLOVER PROTECTION SYSTEM (ROPS)	2-post foldable ROPS standard with seat belt and latch.
	DECK LIFT	Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.
CASTERS	0.50 thick double-yoke, smooth tread caster wheel assembly with pre-installed bearing cups.	
CUP HOLDER	Standard.	
DECKS	STYLE	Full-floating UltraCut Series 6 featuring the heavy-duty Triton [®] spindle. Side discharge standard with the option to bag or mulch.
	WIDTHS AVAILABLE	48", 52", 60" and 72". 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge formed and welded spindle mounting reinforcements for improved strength and reduced weight. 4-point suspension, full floating deck with 6 adjustable, cone-shaped, anti-scalp rollers on 60" & 72." 4-point suspension, full floating deck with 3 adjustable, cone-shaped, anti-scalp rollers on 48" & 52."
	CUTTING HEIGHT	1.0" (2.5 cm) to 5.5" (14 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.
	BLADE-TIP SPEED	Approximately 18,500 fpm.
EQUIPMENT	TRACTOR FRAME	Unibody, welded, heavy-duty 1.5" x 3" tubular steel.
	STEERING AND MOTION CONTROL	Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Levers are also adjustable to 2-height positions.
	FRONT CASTER TIRES	13 x 6.5-6 smooth tread, semi-pneumatic tires on 60" & 72" models; 13 x 5.0-6 smooth tread, semi-pneumatic tires on 48" & 52."
	DRIVE TIRES	24 x 12.0-12, 4-ply Multi-Trac [®] on 60" & 72" models; 24 x 9.5-12, 4-ply Multi-Trac on 48" and 52" models.
	TURNING RADIUS	True zero-turn.
	PARKING BRAKE	Lever-actuated disc brake.
	SEAT	Deluxe, two-tone, bolstered seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.
	DIAGNOSTICS	Operational diagnostics with integral fuel gauge. EFI unit has malfunction indication light (MIL). For propane units, the fuel gauge is located on aluminum tanks.
	BLADE SPINDLES	No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 1.75"-diameter splined blade driver and 1.18" diameter spindle shaft.
	ENGINE OIL	Exmark 4-Cycle Premium Engine Oil.
HYDRAULIC FLUID	Exmark Premium Hydro Oil.	
ELECTRICAL	12-volt battery with 15-amp alternator except Kohler EFI which has 20-amp alternator.	
ENGINE HOURMETER	Standard.	

BEST-SELLING BRAND OF MOWING EQUIPMENT FOR THE LANDSCAPE PROFESSIONAL.

EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark[®] and Lazer Z[®] are registered trademarks, and UltraCut[™] is a trademark of Exmark Mfg. Co., Inc. ©2011 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2011.